

TOP QUALITY SOLUTIONS FOR YOUR LABORATORY






















Distributed By

Polypropylene Ductless Fume Hood



- Polypropylene structure with high chemical resistance
- · Easily dissembled back wall
- Tempered glass sliding front window
- Optional stand
- Monitor displays fan's total operation time, for tracking and filter replacement
- Top quality quiet fan
- Eco-friendly, cost-effective 800 LUX LED lighting separated from the work area
- Wind speed at 0.5±0.1 m/s, 100±20 FPM
- Convient front access for filter replacement
- Top filtration unit including variety of HEPA & carbon filters
- User-friendly digital control system
- EN-14175 / CE / ASHRAE 110-1995 certified



| Model | CF-060-PP | CF-090-PP | CF-120-PP | CF-150-PP | CF-180-PP |
|-----------|------------------|------------------|-------------------|-------------------|-------------------|
| Size (mm) | 600 x 750 x 1223 | 900 x 750 x 1223 | 1200 x 750 x 1223 | 1500 x 750 x 1223 | 1800 x 750 x 1223 |

Polypropylene Ductless Fume Hood with VAV

- Automatic airfow control (VAV system) with user friendly 4.3" color touch screen, settable operating speed, alarm speed, visual and audio alarms.
- Polypropylene structure with high chemical resistance
- Easily dissembled back wall
- Optional stand
- Tempered glass sliding front window
- Top quality, quiet fan
- Eco-friendly, cost-effective 800 LUX LED lighting separated from the work area
- Wind speed at 0.5 m/s, 100 FPM
- Convient front access for filter replacement
- Top filtration unit including variety of HEPA & carbon filters
- EN-14175 / CE / ASHRAE 110-1995 certified



| Model | CF-060-VAV | CF-090-VAV | CF-120-VAV | CF-150-VAV | CF-180-VAV |
|-----------|------------------|------------------|-------------------|-------------------|-------------------|
| Size (mm) | 600 x 750 x 1223 | 900 x 750 x 1223 | 1200 x 750 x 1223 | 1500 x 750 x 1223 | 1800 x 750 x 1223 |



Educational Ductless Fume Hood with All Round Clear Glass

- 360° transparency for exceptional visiblity
- Polypropylene structure with high chemical resistance
- Easily dissembled back wall
- Tempered glass sliding front window
- Optional stand
- Monitor displays fan's total operation time, for tracking and filter replacement
- Top quality quiet fan
- Eco-friendly, cost-effective 800 LUX LED lighting separated from the work area
- Wind speed at 0.5±0.1 m/s, 100±20 FPM
- Convenient front access for filter replacement
- Top filtration unit including variety of HEPA & carbon filters
- User-friendly digital control system
- EN-14175 / CE / ASHRAE 110-1995 certified



| Model | CF-060-CB | CF-090-CB | CF-120-CB | CF-150-CB | CF-180-CB |
|-----------|------------------|------------------|-------------------|-------------------|-------------------|
| Size (mm) | 600 x 750 x 1223 | 900 x 750 x 1223 | 1200 x 750 x 1223 | 1500 x 750 x 1223 | 1800 x 750 x 1223 |



Ecoline Ductless Fume Hood

- Compact cost effective model
- Polypropylene structure with high chemical resistance
- Built-in sealed polypropylene worktop
- Tempered glass front window
- Monitor displays fan's total operation time, for tracking and filter replacement purposes
- Eco-friendly, cost-effective 800 LUX LED lighting
- Wind speed at 0.5±0.1 m/s, 100±20 FPM
- Easy filter replacement
- Top filtration unit including variety of HEPA & carbon filters
- User-friendly digital control system



| Model | ECO-CF-075 |
|-----------|-----------------|
| Size (mm) | 750 x 550 x 900 |

▶ Polypropylene Fume Hood

- Polypropylene structure with high chemical resistance
- One-piece welded structure
- Built-in polypropylene worktop
- Tempered glass slide front sash
- Eco-friendly 800 LUX LED lighting separated from the work area
- Includes polypropylene lower base cabinet
- Optional: sink/water tap/gas tap/vacuum tap
- User-friendly digital control system
- Additional options: VAV system, variety of worktop materials, etc.
- EN-14175, ASHRAE 110-1995 certified



| Model | FH-120-PP | FH-150-PP | FH-180-PP | FH-200-PP | FH-250-PP |
|-----------|------------------|-------------------|-------------------|-------------------|-------------------|
| Size (mm) | 1200 x 805x 2320 | 1500 x 805 x 2320 | 1800 x 805 x 2320 | 2000 x 805 x 2320 | 2500 x 805 x 2320 |

Active Polypropylene Fume Hood

- VAV system including 7" color display screen
- Sensor detects staff presence and opens/closes the window, as well as adjusting fan speed to save energy
- Polypropylene structure with high chemical resistance
- One-piece welded structure
- Built-in polypropylene worktop
- Tempered glass slide front sash
- Eco-friendly, cost-effective 800 LUX LED lighting separated from the work area
- Optional: sink/water tap/gas tap/vacuum tap
- Includes polypropylene lower base cabinet
- Optional: Variety of worktop materials
- EN-14175 / ASHRAE 110-1995 certified



| | Model | FH-120-PP-ACT | FH-150-PP-ACT | FH-180-PP-ACT | FH-200-PP-ACT | FH-250-PP-ACT |
|---|-----------|------------------|-------------------|-------------------|-------------------|-------------------|
| Ī | Size (mm) | 1200 x 805x 2320 | 1500 x 805 x 2320 | 1800 x 805 x 2320 | 2000 x 805 x 2320 | 2500 x 805 x 2320 |

Walk-In Polypropylene Fume Hood

- Large front opening that can contain large, heavy, or tall objects
- Polypropylene structure with high chemical resistance
- · Large front window 1.80 mm high
- One-piece welded structure
- Tempered glass slide front sash
- Eco-friendly 800 LUX LED lighting separated from the work area
- Optional: sink/water tap/gas tap/vacuum tap
- User-friendly digital control system
- Additional options: VAV system, variety of worktop materials
- EN-14175, ASHRAE 110-1995 certified



| Model | FH-120-WI-PP | FH-150-WI-PP | FH-180-WI-PP | FH-200-WI-PP | FH-250-WI-PP |
|-----------|------------------|-------------------|-------------------|-------------------|-------------------|
| Size (mm) | 1200 x 805x 2320 | 1500 x 805 x 2320 | 1800 x 805 x 2320 | 2000 x 805 x 2320 | 2500 x 805 x 2320 |

Metal Fume Hood

- Metal epoxy-coated oven-tempered structure, with an optional polypropylene construction suitable for working with harsh chemicals
- Frontal tempered glass window, sliding horizontally on tracks
- Air suction from both the top and back panel
- LED lighting at 800 LUX, with optional rupture protection
- Side walls coated with 6 mm HPL
- Epoxy work surface with edges sloping towards the workspace, with options for HPL/stainless steel/polypropylene/ceramic
- Control panel including an on/off unit power and light switch, optional VAV system
- Includes metal lower base cabinet
- EN-14175, ASHRAE 110-1995 certified



| Model | FH-120 | FH-150 | FH-180 | FH-200 | FH-250 |
|-----------|-------------------|-------------------|-------------------|-------------------|-------------------|
| Size (mm) | 1200 x 800 x 2320 | 1500 x 800 x 2320 | 1800 x 800 x 2320 | 2000 x 800 x 2320 | 2500 x 800 x 2320 |

Polypropylene Fume Hood with Wet Scrubber

- Wet scrubber functionality, comprising: Spray Nozzles | Upper Eliminator | Scrubbing Media | Water Pump | Water Tank | Visual & Audio Alarm for Low Water Level
- Wide surface for extended reach
- Low noise system
- Low pressure drop
- Polypropylene structure with high chemical resistance
- One-piece welded polypropylene structure
- Built-in polypropylene worktop
- Tempered glass sliding front sash
- Eco-friendly, cost-effective 800 LUX LED lighting
- Compact
- Easy access for maintenance and repairs
- EN-14175, ASHRAE 110-1995 certified






| Model | FH-120-WS | FH-150-WS | FH-180-WS | FH-200-WS | FH-250-WS |
|-----------|------------------|-------------------|-------------------|-------------------|-------------------|
| Size (mm) | 1200 x 805x 2320 | 1500 x 805 x 2320 | 1800 x 805 x 2320 | 2000 x 805 x 2320 | 2500 x 805 x 2320 |

Polypropylene Laminar Airflow Fume Hood

- Clean bench functionality
- Polypropylene structure with high chemical resistance
- One-piece welded structure
- Built-in polypropylene worktop
- Tempered glass slide front sash
- Eco-friendly 800 LUX LED lighting separated from the work area
- Includes polypropylene lower base cabinet
- Optional: sink/water tap/gas tap/vacuum tap
- User-friendly digital control system
- Additional options: VAV system, variety of worktop materials







Polypropylene Biosafety Cabinet Class A2

- Polypropylene structure, tempered glass side walls
- 304 stainless steel work surface & spill tray
- Two H14 HEPA filters
- Advanced EC fan with 304 stainless steel housing
- Smart 7" control system with touch screen
- Maintenance & technical faults alarms
- Timers and counters management screen
- Germicidal water proof UV light system and safety interlock mechanism
- 6 mm double layer safety front glass window with electrical motion system
- Programmable economical night mode
- **Economical LED light**
- Airflow Pattern: 70% circulation, 30% exhaust
- Adjustable stand
- ISO 5/CLASS 100 cleanliness level according to ISO 14644-1 & USA Federal Standard 209E
- EN 12469 & CE certified

| Model | BO-090-PP | BO-120-PP | BO-150-PP | BO-180-PP |
|-----------|------------------|-------------------|-------------------|-------------------|
| Size (mm) | 925 x 850 x 2280 | 1225 x 850 x 2280 | 1525 x 850 x 2280 | 1825 x 850 x 2280 |



Polypropylene Biosafety Cabinet Class B2

- Polypropylene structure, tempered glass side walls
- 304 stainless steel work surface & spill tray
- Two H14 HEPA filters
- Advanced EC fan with 304 stainless steel housing
- Smart 7" control system with touch screen
- Technician calibration screen
- Maintenance & technical faults alarms
- Timers and counters management screen
- Germicidal water proof UV light system and safety interlock mechanism
- 6 mm double layer safety front glass window with electrical motion system
- Programmable economical night mode
- **Economical LED light**
- Airflow pattern: 100% exhaust
- Adjustable stand
- ISO 5/CLASS 100 cleanliness level according to ISO 14644-1 & USA Federal Standard 209F

| • | EN 12469 & CE cert | - | | | |
|---|--------------------|------------------|-------------------|-------------------|-------------------|
| | Model | BO-090-PP-B | BO-120-PP-B | BO-150-PP-B | BO-180-PP-B |
| | Size (mm) | 925 x 850 x 2290 | 1225 x 850 x 2290 | 1525 x 850 x 2290 | 1825 x 850 x 2290 |
| | | | | | |



Ecoline Biological Safety Cabinet Class II A2

- Polypropylene structure with high chemical resistance
- 304 stainless steel work surface & spill tray
- Two H14 HEPA filters
- Advanced EBM fan
- Smart 4.3" touch-screen control system
- Technician calibration screen, fault alarms
- Germicidal UV light system and safety interlock mechanism
- 6 mm double layer safety front glass window with electrical motion system
- **Economical LED light**
- ISO 5/ CLASS 100 cleanliness level according to EN 12469 standards

| Model | ECO-BO-070 |
|-----------|------------------|
| Size (mm) | 700 x 660 x 1200 |





PCR Unit - UV

- Polypropylene structure with high chemical resistance
- Ozone free UV lightbulb, UV output at 1M 254nm
- Tempered glass frameless pivot window
- Eco-friendly, cost-effective 800 LUX LED lighting
- Smart safety mechanism prevents UV exposure
- User-friendly control panel with UV, lighting control & UV timer (30 min)
- Optional stand



| Model | PCR-060-UV | PCR-090-UV | PCR-120-UV |
|-----------|--------------------|--------------------|---------------------|
| Size (mm) | 600 x 640 x 750 mm | 900 x 640 x 750 mm | 1200 x 640 x 750 mm |

PCR Unit -HEPA

- Top filtration unit including variety of HEPA & carbon filters
- Polypropylene structure with high chemical resistance
- Ozone free UV lightbulb, UV output at 1M 254nm
- Tempered glass frameless pivot window
- Eco-friendly, cost-effective 800 LUX LED lighting
- Air velocity: 0.45±0.1 m/s, 90±20 FPM
- Smart safety mechanism prevents UV exposure
- User-friendly control panel with UV, lighting control & UV timer (30 min)
- Optional stand
- ISO 6/ CLASS 1000 cleanliness level according to ISO 144641 and USA Federal Standard 209E



| Model | PCR-060-HEPA | PCR-090-HEPA | PCR-120-HEPA |
|-----------|--------------------|-----------------|------------------|
| Size (mm) | 600 x 640 x 900 mm | 900 x 640 x 900 | 1200 x 640 x 900 |

▶ Lab Storage Cabinet

- Polypropylene structure with high chemical resistance
- Door locks
- · Ventilation openings at the top and bottom of the cabinet
- Three stationary shelves inside the cabinet

| Model | LFC-PF-900-PP | LFC-PF-1200-PP | LFC-PF-1600-PP |
|-----------|------------------|-------------------|-------------------|
| Size (mm) | 900 x 450 x 1800 | 1200 x 450 x 1800 | 1600 x 450 x 1800 |

With Filtration System

(including carbon/HEPA filters and powerful economical consumption fan)

| Model | LFC-AFF-900-PP | LFC-AFF-1200-PP | LFC-AFF-1600-PP |
|-----------|------------------|-------------------|-------------------|
| Size (mm) | 900 x 450 x 2100 | 1200 x 450 x 2100 | 1600 x 450 x 2100 |



Metal/Polypropylene Horizontal Laminar Clean Bench



- Horizontal air stream producing clean air as per SO5/ CLASS100 or ISO4/Class10 standards (depending on filter installed).
- Massive epoxy coated, oven-tempered metal or polypropylene structure
- User-friendly digital control system
- Work surface made of 304 stainless steel
- Side windows made from tempered glass
- High quality, quiet fan
- Noise level < 58 DBA
- Optional stand
- · Variety of sizes and materials; universal electrical outlet
- Eco-friendly, cost-effective LED lighting
- Compliance with production/test standard: US Federal Standard 209E / ISO-14644-1



| Metal Models | HC-H090 | HC-H120 | HC-H160 | HC-H180 |
|----------------------|-------------------|-------------------|-------------------|------------------|
| Size (mm) | 1030 x 930 x 1110 | 1330 x 930 x 1110 | 1630 x 930 x 1110 | 1930 x930 x 1110 |
| | 1 | | | |
| Polypropylene Models | HC-H090P | HC-H120P | HC-H160P | HC-H180P |

Metal/Polypropylene Vertical Laminar Clean Bench

- Vertical air stream producing clean air at ISO5/ CLASS100 or ISO4/ Class10 standards
- Massive epoxy-coated and oven tempered metal or polypropylene structure
- User-friendly digital control system
- Work surface made of 304 stainless steel
- Side windows made of tempered glass
- · High quality, quiet fan
- Noise level < 58 DBA
- Optional stand
- Variety of sizes and materials; universal electrical outlet
- Eco-friendly, cost-effective LED lighting
- Compliance with production/test standard: USA Federal Standard 209E / ISO-14644-1



| Metal Model | HC-V090 | HC-V120 | HC-V160 | HC-V180 |
|-------------|-------------------|-------------------|-------------------|-------------------|
| Size (mm) | 1000 x 760 x 1250 | 1300 x 760 x 1250 | 1600 x 760 x 1250 | 1900 x 760 x 1250 |

| Polypropylene Model | HC-V090P | HC-V120P | HC-V160P | HC-V180P |
|---------------------|-------------------|-------------------|-------------------|------------------|
| Size (mm) | 1000 x 760 x 1250 | 1330 x 760 x 1250 | 1630 x 760 x 1250 | 1930 x760 x 1250 |

► VAV - Auto Air Velocity Control System

- 4.3"/7" color touch screen with display and control for set point, air velocity, alerts and configuration information
- High quality frequency inverter
- A variety of HOTWIRE sensor systems which enables changes according to customer requests
- Simple user friendly interface
- Can renovate an existing system
- Cost effective as it includes a high-end frequency inverter
- Frequency inverter maximizes efficiency and prevents motor noises



| P/N | VAV-CI-4.3 | VAV-CI-7 |
|-------------|---|---|
| Screen size | 4.3" | 7" |
| Function | Auto air velocity control systems (VAV and VFD) | Auto air velocity control systems (VAV + VFD) and central operating system for fume hoods |

Airflow Alarm

- Elegant glass panel
- Simple user friendly interface
- Accuracy- + 0.07 m/s
- Visual display green and red LEDs
- Alarm indications LED and audible alarm
- Input power 230/115 VAC, 50/60hz

| P/N | Description |
|--------------|--|
| VA-AFA-LH-CI | Advanced system providing alerts on low/high-level airflow in the fume hood. |
| VA-AFA-L-CI | Basic system providing alerts on low-level airflow in the fume hood. |





Filter Alarm

- Detects and alerts on concetration of a variety of chemicals & gasses
- Elegant glass panel
- Simple user friendly interface
- Max sensitivity 50 ppm
- · Visual display Green and red LEDs
- Alarm indications LED and audible alarm
- Input power 230/115 VAC, 50/60 hz



| P/N | Description |
|-----------|--------------------------------------|
| VA-FLA-CI | Filter alarm for ductless fume hoods |



Aluminum Cyanoacrylate Fuming Chamber



- Control system displays all parameters of the processing cycle.
 Adjustments to the presets can quickly be performed.
- Can be activated automatically, or manually with an option for temperature and humidity control
- Filtering system with a carbon filter
- Eco-friendly, cost-saving LED lighting
- Programmable Electronic Control with user-friendly on-screen functions to program the Purge Cycle, Contact Time and RH Sensor
- Main and Pre Filters are supplied as standard with all chambers
- CE certified



| Model | SG-060 | SG-075 | SG-090 | SG-150 | SG-180 |
|-----------|-----------------|------------------|------------------|-------------------|-------------------|
| Size (mm) | 600 x 600 x 760 | 750 x 750 x 1550 | 900 x 750 x 1550 | 1500 x 750 x 1550 | 1800 x 750 x 1550 |



Polypropylene Cyanoacrylate Fuming Chamber

- Control System displaying all parameters of the processing cycle.
- Can be activated automatically, or manually with an option for temperature and humidity control
- Filtering system with a carbon filter
- · Eco-friendly, cost-saving LED lighting
- Alarm for end of automatic cycle
- Audio-Visual 30-second alarm
- Programmable Electronic Control with user-friendly on-screen functions to program the Purge Cycle, Contact Time and RH Sensor.
- Main and Pre Filters are supplied as standard with all chambers
- CE certified



| Model | SG-060-P | SG-075-P | SG-090-P | SG-150-P | SG-180-P |
|-----------|-----------------|------------------|------------------|-------------------|-------------------|
| Size (mm) | 600 x 600 x 760 | 750 x 750 x 1550 | 900 x 750 x 1550 | 1500 x 750 x 1550 | 1800 x 750 x 1550 |



Water Filtration - Cyanoacrylate Fuming Chamber

- Cyanoacrylate vapors are filtered using water filtration, ensuring no dangerous substances are exhausted into the atmosphere.surrounding the laboratory
- Control system displaying all parameters of the processing cycle
- Automatic heating control is determined according to the amount of cyanoacrylate placed in the chamber
- Automatic temperature control Humidity control ensures ± 3% humidity
- Eco-friendly, cost-saving LED lighting
- CE certified



| Model | SG-060-WF | SG-075-WF | SG-090-WF | SG-150-WF | SG-180-WF |
|-----------|-----------------|------------------|------------------|-------------------|-------------------|
| Size (mm) | 600 x 600 x 760 | 800 x 750 x 1550 | 900 x 750 x 1550 | 1500 x 750 x 1550 | 1800 x 750 x 1550 |



Evidence Drying Cabinet

- · Polypropylene structure with high chemical resistance
- Clear triplex safety glass
- Double location HEPA filter supply and exhaust.
- Internal RH and temperature display
- Top quality purge fan
- UV sterilization + safety interlock mechanism
- Bottom draining basin with tap
- Super dry system (SD)
- Electrical 110/220V, 60/50hz



| Model | EV-090 | EV-120 | EV-180 |
|-------|------------------|-------------------|-------------------|
| mm | 900 x 1240 x 850 | 1200 x 1240 x 850 | 1800 x 1240 x 850 |

With Fast Super Dry System (SD)

| Model | EV-090-SD | EV-120-SD | EV-180-SD |
|-------|-------------------|-------------------|-------------------|
| mm | 1000 x 1240 x 850 | 1200 x 1240 x 850 | 1800 x 1240 x 850 |



Downflow Unit

- Polypropylene structure with high chemical resistance
- Worktop 304 SUS
- Filters H14 HEPA/ carbon
- Fans Top quality, quiet centrifugal fan
- Alarm High pressure (filter block)
- Light 24w LED
- Convient front access for filter replacement
- User-friendly digital control system
- Electrical 110/220v, 60/50hz



| Model | DF-60 | DF-90 | DF-120 |
|-----------|------------------|------------------|-------------------|
| Size (mm) | 600 x 700 x 1200 | 900 x 700 x 1200 | 1200 x 700 x 1200 |

Outdoor Centrifugal Fan & Electromechanical Motor

- Roof/side wall fans
- Weather resistant PVC structure and polypropylene impeller.
- A 3-phase motor with water protection level of IP 44/55 operates at 380 VAC.
- Sound level 70 dBa
- Variety of sizes, flows and accessories
- Exceptional performance, low vibration levels, low noise levels,
- Long service life, high reliability, convenient maintenance
- Large breakaway torque
- Fixing measurements and power grade comply with IEC standard.
- Rated frequency: 50Hz or 60Hz
- Cooling method: IC411 (cooled by self fan)
- Power 1.5.KW or 2.2.KW
- Weight: 28/34 kg





NEW FROM TOPAIR SYSTEMS!

Polypropylene Laminar Airflow Fume Hood



Biosafety Cabinet - Class B2



Ecoline Ductless
Fume Hood



Ecoline Ductless Biosafety cabinet



Educational Ductless Fume Hood with All Round Clear Glass







