Polypropylene Vertical Laminar **Clean Bench**



TopAir provides high-quality, safe Vertical Laminar Clean Benches. TopAir's clean benches suck air from the room or hall space, transfer the air through a HEPA filter using a fan, and then clean the bench area with filtered air.

In vertical benches, the filtered air is channeled downwards through a filter installed at the top of the bench. All components are produced by leading global companies, such as AAF USA.


Advanced Operation System:

- Color 5" touch screen
- 10-speed fan
- Hour counter for filter
- Filter replacement alarm

Clean benches are designed to supply a clean controlled work environment meeting Class 100/ISO5 cleanliness standard, resembling a clean room, with the additional advantages of portability and small dimensions.

Clean benches provide a high quality alternative to a clean room at a much lower cost and without massive Vertical air stream producing clean air at ISO-5/ CLASS100 or ISO4/Class10 standards

- Polypropylene structure with high chemical resistance
- Work surface made of 304 stainless steel
- Side windows made of tempered glass
- High efficiency quiet EC fan
- Optional stand
- Universal electrical outlet
- Innovative, advanced design
- Variety of sizes and materials
- Eco-friendly, cost-effective LED lighting
- Compliance with Test Standard: US Federal Standard 209E / ISO 14644-1 / CE



Models

Spec/Model	HC-V090P	HC-V120P	HC-V150P	HC-V180P			
Outer Dimensions	900 x 760 x 1250 mm	1200 x 760 x 1250 mm	1500 x 760 x 1250 mm	1800 x760 x 1250 mm			
WxDxH	35.4 x 30 x 49.2"	47.2 x 30 x 49.2"	59 x 30 x 49.2"	70.8 x 30 x 49.2"			
WE CAN CUSTOMIZE TO ANY SIZE - EVEN A SINGLE UNIT! CONTACT US FOR DETAILS							
Workspace	770 x 660 x 750 mm	1070 x 660 x 750 mm	1370 x 660 x 750 mm	1670 x 660 x 750 mm			
(W x D x H)	30.3 x 26 x 29.5"	42.1 x 26 x 29.5"	53.9 x 26 x 29.5"	65.7 x 26 x 29.5"			
Test Standard	USA Federal Standard 209E / ISO-14644-1, CE						
Air Velocity m/s	0.3 m/s, 60 FPM						
Cleanliness in Workstation	Class-100 (FS 209E) ISO 4, ISO-14644-1						
Hood Material	Polypropylene						
Work Table Material	Stainless steel SUS 304						
Noise (Tested 20 cm from the work table, 1.2m above ground)	<50dB	<50dB	<54dB	<54dB			
Power Supply	110 / 220V, 50/60 Hz, Single phase						
Illumination	800 LUX LED lighting						
Filter	HEPA Filter Efficiency of 99,9995% at 0.3 Microns H14 (Optional ULPA filter)						

Accessories

Spec/Model	HC-090	HC-120	HC-150	HC-180
Stand	HC-090-ST	HC-120-ST	HC-150-ST	HC-180-ST
Combined UV light and front sash	HC-090-UV-FS	HC-120-UV-FS	HC-150-UV-FS	HC-180-UV-FS
Separated "floating" table	HC-090-VB	HC-120-VB	HC-150-VB	HC-180-VB

Tel:+1-855-6-TOPAIR (+1-855-686-7247) Email: sales@topairsystems.com
Web: www.topairsystems.com | Headquarters USA: 8912 68th Avenue Forest Hills New York 11375, USA